



## TEMPORARY DRAWING

THIS IS A SUGGESTED DESIGN FOR CUSTOMER APPROVAL. FINAL SIZES AND SPECIFICATIONS ARE SUBJECT TO FINAL PRODUCTION QUALIFICATIONS.

NOTES: MATERIAL: HDPE

SUGGESTED SOURCE: EQUISTAR 5602 (WITH 25% PCR ADDED) COLOR: WHITE TO MATCH COLOR CHIP SUPPLIED BY THETFORD CORPORATION. SEALING SURFACE OF BOTTLE NECK MUST BE SMOOTH AND FREE OF BURRS AND IRREGULARITIES AND FLAT WITHIN .010 T.I.R. WITH RESPECT TO A PLANE

PERPENDICULAR TO THE THREADED AXIS.
ANY NONFLATNESS MUST BE GRADUAL AT A RATE NOT TO EXCEED .001 PER
3' ARC LENGTH ALONG THE SEALING SURFACE

.015 ABSOLUTE MINIMUM WALL THICKNESS. REF. P/D # 28575

	$\vdash$		+					
	$\vdash$		+					
	NO.	REV. B	DESCRIPTION				DATE	
	NEC	K FINISH	<b>i:</b> M28 SP4	00 (SPECIAL)	) (SPECIAL)		<b>WT.</b> 19.0	±1g
	'T'		'E'	'H'		's'	,Ľ,	'W'
	1.078 ±.010		.987 ±.007	.490 ±.015	.046	±.015	.500 ±.015	
	27.3	8 ±0.25	25.07 ±0.18	12.45 ±0.38	1.17	±0.38	12.70 ±0.38	
	HELIX <b>&lt;</b> : 2° 57' T.P.I.: 6 CUTT. DIA.: .500[12.70]							[12.70]
	CAPACITY TO FILL LEVEL BEFORE DECORATING 236.50 ±7ml							50 ±7ml
	CAF	CAPACITY TO FILL LEVEL AFTER DECORATING —						
	OVE	OVERFLOW CAPACITY BEFORE DECORATING 267.0						
	OVERFLOW CAPACITY AFTER DECORATING							
DRAWING CHECKED SPECIFICALLY FOR:								
NECK FINISH								
WEIGHT								
CAPACITY								
MATERIAL								
SPECIAL REQUESTS	DRAWN BY: 255 DESC. O MODERN DOLLND							LINID
PRODUCT DESIGN TO BE APPROVED BEFORE MOULD CAVITIES ARE MACHINED.	COALE 1 10 A TE DEC 20 /05				8 oz. MODERN ROUND			
APPROVED BY	130A	SCALE: 1:1DATE: DEC 22/05 DRAWING NO. 12 — 30758—PD						
DATE	ВОТ	BOTTLE MAT'L: HDPE						
This drawing subject to standard industry tolerances	CAD	NAME: I	PD\12-3075		NO. 1	12 - 3	0758 - 3	3